

01-07-00

EJ 18764571605

1/6/00

A

## IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Docket No. AUS990884US1

Assistant Commissioner for Patents  
Washington, D.C. 20231

Sir:

Transmitted herewith for filing is the patent application of Inventor(s):

**Daniel Knabenbauer**For: **THREE-DIMENSIONAL DISPLAY APPARATUS**

Enclosed are also:

- ☒ 22 Pages of Specification including an Abstract  
☒ 8 Pages of Claims  
☒ 11 Sheet(s) of Drawings  
☒ A Declaration and Power of Attorney  
☒ Form PTO 1595 and assignment of the invention to IBM Corporation

**CLAIMS AS FILED**

FOR	Number Filed		Number Extra		Rate		Basic Fee <del>(\$760)</del> 690
Total Claims	49	-20 =	29	X	\$ 18	=	\$522
Independent Claims	2	-3 =	0	X	\$ 78	=	0
Multiple Dependent Claims	0			X	\$260	=	0
<b>Total Filing Fee =</b>							<del>\$1282.00</del>

- ☒ Please charge ~~\$1282.00~~ 1212 to IBM Corporation, Deposit Account No. 09-0447 0451  
☒ The Commissioner is hereby authorized to charge payment of the following fees associated with the communication or credit any over payment to IBM Corporation, Deposit Account No. 09-0447. A duplicate copy of this sheet is enclosed.  
☒ Any additional filing fees required under 37CFR § 1.16.  
☒ Any patent application processing fees under 37CFR § 1.17.

Respectfully,

Votel Emile

Reg. No. 39,969


Intellectual Property Law Dept.

IBM Corporation

11400 Burnet Road 4054

Austin, Texas 75758

Telephone: (512) 823-1005



09477570 "010600"

**Three-Dimensional Display Apparatus****BACKGROUND OF THE INVENTION**

5

This application is related to co-pending and commonly assigned U.S. Patent Application Serial Nos. \_\_\_\_\_ (Attorney Docket Nos. AUS990876US1 and AUS990883) filed concurrently herewith and hereby incorporated by reference.

10

**1. Technical Field:**

The present invention is directed to a three-dimensional display apparatus. In particular, the present invention is directed to a display comprised of a plurality of pixels, each pixel being comprised of a plurality of cells, which is capable of displaying an image in three-dimensions.

15

**20 2. Description of Related Art:**

The ability to accurately recreate images in three dimensions has long been sought after. Three-dimensional displays may be very important in such areas as entertainment, medical imagery, architectural design, and a plethora of other areas. The result of this long felt need for three-dimensional displays has been the development of advanced ways of tricking the human brain into believing that the images seen by the eye are in three dimensions.

25

For example, computers may use perspective drawing techniques to represent three dimensions on a two dimensional screen. Some pictures and optical illusions, when stared at, give the impression of some depth due to

30

094750-010000

Thus, the attempts at creating three-dimensional imagery have failed at creating an actual  
10 three-dimensional display and must therefore, rely on tricks to fool the human brain into believing what is seen is a three-dimensional image. In view of the above, it would be advantageous to have a method and apparatus to provide an actual three-dimensional image.

**SUMMARY OF THE INVENTION**

5       The present invention provides a three-dimensional display apparatus that does not require tricks or illusions to represent objects in three dimensions. The display is comprised of a plurality of pixels which are, in turn, comprised of a plurality of cells.

10       The cells include a plurality of cell walls, a cell lens wall and a cell base. The cells further include an anode and a cathode. The cell is filled with a gas that is excited by electrical discharges. A phosphorus material is applied to the anode, or nearby the anode,  
15       such that when an electrical discharge is created between the anode and the cathode, the gas is electrically excited causing the gas to emit ultraviolet radiation. The ultraviolet radiation causes the phosphorus material to emit visible light according to a color of the  
20       phosphorus material. An anode having a phosphorus material of a certain color applied to it or nearby it will be identified by the color of the phosphorus material. Thus, for example, an anode having a red colored phosphorus material applied to it will be  
25       identified as a red anode.

      A plurality of cells are combined to create a pixel. Each pixel has at least one cathode and at least one anode of each color red, green and blue. By controlling the intensities and durations of the charge to each of  
30       the anodes of the respective colors red, green and blue, every color in the visible spectrum is producible. The

009979 0157460

5       A plurality of the pixels are combined to create a  
three-dimensional display. The three-dimensional display  
is controlled by a control system that determines which  
of the pixels to turn on and which to turn off, as well  
as the intensities of the light that the cells of the  
10       pixels produce and the duration of their illumination.  
Based on this determination, the control system sends  
electrical signals along addressable anode bus lines,  
cathode lines, and the like, to cause the selected pixels  
to illuminate. The combination of illuminated pixels,  
15       which are three-dimensional light sources, in a  
three-dimensional matrix creates a three-dimensional  
display. The three-dimensional display is an actual  
three-dimensional display and is not based on optical  
illusions or perspective trickery.

**Figures 2A and 2B** are exemplary diagrams of a pixel;

**Figure 4** is an exemplary block diagram of a control system for controlling the operation of the three-dimensional display;

**Figures 6-9** illustrate a method of manufacturing the three-dimensional display apparatus according to the invention; and

**Figure 10** is an exemplary diagram of an alternative embodiment of a pixel and a cell contained within the pixel according to the invention.

### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

5       The present invention is a hierarchy of devices which build upon each other. The three-dimensional display of the present invention is comprised of a plurality of pixels which are, in turn, comprised of a plurality of cells. Thus, the following description will  
10 address each of these building blocks from the cell to the display separately for clarity.

#### Three-Dimensional Display Cell

15       **Figure 1** is an exemplary diagram of a cell **100** according to the present invention. As shown in **Figure 1**, cell **100** is comprised of a cell base **110**, a plurality of cell walls **120**, a cell lens wall **130**, an addressable anode **140** and a cathode **150**. Cell **100** has a truncated pyramidal shape with the volume created by the cell base  
20 **110**, cell walls **120** and cell lens wall **130**. The volume is filled with a gas, such as Xenon gas, or the like, that emits ultra-violet radiation when electrically excited.

25       Although **Figure 1** shows the cell **100** as having a large height, the dimensions of the cell **100** in **Figure 1** are exaggerated for clarity of description of the elements **110-150**. In a preferred embodiment, the height is less than one half the length or width of the cell base **110** in order to ensure that the cell **100** may be  
30 combined with other cells **100** to create a pixel. Furthermore, **Figure 1** shows the cell base **110**, cell walls

009970 02450

120, and cell lens wall 130 as being without thickness while in actuality the cell base 110 and cell walls 120-130 will have a thickness due to the materials used in their construction.

5       The cell base 110 and cell lens wall 130 are constructed from a transparent material such that light emitted from the cell 100 may pass through the transparent material. The transparent material may be, for example, glass or the like. With the cell lens wall 10   130, light passing through the transparent material is reflected back through the cell lens wall 130 by a lens, described hereafter. With the cell base 110, the light passing through the transparent cell base 110 is emitted as visible light which is perceivable by the human eye.

15       Although the above described embodiment utilizes a cell lens wall 130 made of a transparent material, the invention is not limited to such an embodiment. Rather, the cell lens wall 130 may be the lens itself. Thus, the cell 100 may have an opening at the apex of the cell 100 20 which may be used to accommodate the placement of the lens. However, for purposes of describing the invention, it will be assumed that the cell lens wall 130 is a separate cell wall located at the apex of the cell 100.

      The cell lens wall 130 may be flat as shown in 25 **Figure 1** or may have various different shapes depending on the type and size of the lens used with the cell 100. For example, if a spherical lens is used, the cell lens wall 130 may have a curvature protruding into the cell 100 volume to thereby accommodate the curvature of the 30 lens. Similarly, if a lens is omitted, a cell lens wall

009070"010600

Docket No. AUS990884US1

**130** is not needed, and the cell walls **120** may continue the pyramidal shape of the cell **100** to a pointed vertex where the lens would have been centered.

The cell base **110** and cell walls **120** are comprised  
5 of a dielectric material which is transparent to visible light and which reflects or absorbs ultraviolet light. This allows the visible light from a first cell **100** to blend with a second cell **100** while preventing the ultraviolet light from the first cell **100** from  
10 interfering with the operation of the second cell **100**. For example, the cell walls **120** may be constructed from a glass material coated with an ultraviolet light blocker or absorption material (such as is currently used in the construction of sunglasses and prescription glasses).  
15 The coating is clear and does not affect the tint of the material.

The dielectric properties of the material of the cell base **110** and the cell walls **120** aid in containing the electric discharges within the cell. In this way,  
20 the electric discharges of one cell will not interfere with the operation of a neighboring cell when the cells are placed in a matrix formation.

The cell further includes a phosphorus material which is used to emit visible light when an electrical  
25 discharge is created between the addressable anode **140** and cathode **150**. The phosphorus material may be placed near the addressable anode **140**, such that the electrical discharge passes through the phosphorus material. Alternatively, the phosphorus material may be placed on  
30 one or more of the cell walls **120** or a portion of one or more of the cell walls **120** such that the electrical

00947570-010600

The electrical circuitry necessary to cause the cell 100 to function may be placed in any location on the cell walls 120 or in the seams between the cell walls 120, the seams between the cell walls 120 and the cell lens wall 130 or the cell base 110, by using microchip technology. Such circuitry is readily apparent to those of ordinary skill in the art and may comprise fine wires, resistors, and the like, along with cathode electrical lines and an addressable anode bus line. The electrical connections are preferably transparent to the human eye such that they are not perceived when the cell 100 is viewed in a normal viewing manner.

The operation of the cell **100** is similar to that of cells in plasma displays, such as the plasma display described in The Electrical Engineering Handbook, Second Edition, CRC Press, 1997, pages 1939-1950, which is hereby incorporated by reference. Specifically, the addressable anode **140** is selectively positively charged when a signal is sent to the addressable anode **140** by way of an anode bus line (not shown). As a result, electrons from the cathode **130** are attracted to the addressable

Docket No. AUS990884US1

anode **140** thereby creating an electrical discharge and an excitation of the gas filled volume in a cell **100**.

Because of the electrical excitation, the gas in the cell **100** emits ultraviolet radiation which causes the phosphorus material in the cell to emit visible light  
5 corresponding to the color of the phosphorus material. The visible light emitted by the phosphorus material is focused by the lens (if present) to pass through the cell base **110** such that the light is perceivable by the human  
10 eye.

The intensity and duration of the light emitted from the phosphorus material can be controlled by controlling the intensity and duration of the electrical discharge. Thus, by controlling the signal from the anode bus line  
15 to the addressable anode **140**, the intensity and duration of the cell **100** emissions can be controlled.

The cell **100** emits visible light corresponding to the color of the phosphorus material in the cell **100**. When a plurality of these cells **100** are combined, one  
20 cell **100** having, for example, a red phosphorus material, another having a green phosphorus material, and a third having a blue phosphorus material, by controlling the intensities of the light emitted from each of these cells **100**, all of the colors in the visible spectrum may be  
25 produced. The combination of cells **100** is referred to herein as a pixel of the three-dimensional display.

#### Three-Dimensional Display Pixel

**Figures 2A** and **2B** are exemplary diagrams of a pixel  
30 **200** according to the present invention. As shown in **Figure 2A**, the pixel **200** is comprised of a plurality of

0947570.010600

Docket No. AUS990884US1

cells **100** with each face of the cube being a cell base **110**. For example, in the cube structure of **Figure 2A**, six cells are combined to create the pixel **200** (one cell for each face of the cube).

5        Only three of the cells **100** are necessary for creating the visible light that will be emitted by the pixel **200** even though the light will be emitted in all six directions from the center of the pixel. Thus, for example, cells **210**, **220** and **230** in **Figure 2B**,  
10        corresponding to cells having a green phosphorus material, blue phosphor and red phosphorus material, respectively, are used to create any color in the visible spectrum. The auxiliary cells **240-260** may be used for auxiliary anodes, wiring, and other circuitry used to  
15        operate the pixel **200**. Alternatively, the auxiliary cells **240-260** may be removed to provide further space for circuitry or to allow for larger cells **100** having a larger gas volume. However, a singular three-dimensional geometry should be maintained for all pixels **200** such as,  
20        for example, a cube.

Each of the cells **210-230** has a corresponding addressable anode **270-290**. A single cathode **295** is used to power each of the cells **210-230**. Thus, for example, when the cathode **295** is powered and the addressable anode  
25        **270** receives a signal, the cell **210** is caused to emit a green light. Similarly, when addressable anodes **280** and **290** receive signals, the cells **220** and **230** are caused to emit blue and red lights, respectively. The light from each of the cells **210-230** is combined to create a single  
30        pixel color that is seen by the human eye. Thus, by

094750-010600

Docket No. AUS990884US1

controlling which cells **210-230** illuminate and the intensities of each of the illuminations, various colors of the visible spectrum are perceived by a viewer.

Although a single cathode **295** is utilized with each  
5 of the cells **210-230**, the invention is not limited to such an embodiment. Rather, depending on the implementation, each cell may have its own dedicated cathode **295**. A single cathode **295** is preferred in this embodiment because it simplifies the overall design and  
10 reduces the amount of materials necessary to create the pixel **200**. However, power constraints and potential problems with stray discharge may require that one or more of the cells **100** in a pixel **200** have their own cathode **295** or share their cathode **295** with a limited  
15 number of other cells **100**.

The cells **210-260** are centered around a lens **298** which can focus the visible light emitted from the phosphorus material through the cell bases **110** (faces of the cube). The lens **298** may have, for example, a  
20 refractive core and utilize different thickness of materials for determining the focusing of the lens **298**. For example, the lens **298** may have a crystalline substrate for a core that provides refractive qualities similar to diamonds. The light reflected from the  
25 crystalline core will be reflected at multiple different angles which intersect at several points thereby blending the colors of light together. The lens material surrounding the core may then map the outermost planes of the crystalline substrate to the plane of the pixel walls  
30 making the pixel walls appear brightest, thereby giving the pixel its cubical lighted shape.

09477570.010600

The lens **298** may be spherical (as shown) or may be any other geometric configuration that allows for the focusing of light through each of the cells **210-260**. For example, the lens **298** may be cubical or hexagonal in shape. The cell lens walls **130** for each of the cells **210-260** is shaped to accommodate the shape of the lens **298** or lack thereof.

Because the lens **298** focuses the light emitted by the phosphorus material onto the cell bases **130**, i.e. the faces of the pixel, a three-dimensional light source is created. When a plurality of pixels are combined, each having a three-dimensional light source, the result is a three-dimensional image. The thickness of the cell bases **110**, i.e. the faces of the cube, provide enough distance between the pixels **200** such that the colors of the pixels do not blend into one another and the pixels are distinguishable.

#### Three-Dimensional Display

**Figure 3** is an exemplary diagram of a three-dimensional display **300** according to the present invention. As shown in **Figure 3**, the display **300** is comprised of a plurality of pixels **310-370**. These pixels are implemented using pixel **200** from **Figure 2**. Each of the pixels **200** has a red, blue, and green anode (designated in **Figure 3** as a circle with an R, B or G) and a cathode (designated by a circle with a C). The front face of the pixels **310-370** are shaded for clarification purposes only and the actual display will not require additional shading of the pixel face.

Additionally, the cube structure of the display **300** is cut away in **Figure 3** to aid in understanding the structure of the display **300**. In actuality, the display **300** may be a complete cube or may be any other geometric configuration. For example, the display **300** may be rectangular, rhomboidal, or the like. The lenses of the pixels are not shown in **Figure 3** for clarity in illustrating the invention.

As shown in **Figure 3**, up to eight adjacent cells may share an anode and/or a cathode. Furthermore, pixels **310-370** may share pixel faces and hence, share the pixel face materials. For example, the top face of pixel **310** may also be the bottom face of pixel **320**. This arrangement of pixels **310-370** minimizes the amount of materials necessary to produce the display **300**, reduces the complexity of the overall display **300**, and thereby reduces the cost of producing the display **300**.

Microchip technology may be used to create connections between pixels, cells, signal sources and power sources along the seams between pixels **310-370** and/or in the cell walls or auxiliary cells. In particular, the seams between anodes may be used to hold an addressable anode bus line for addressing the anodes to thereby turn the cells of the pixels **310-370** on and off and to control the intensity and duration of the illumination of the pixels.

It should be noted that each addressable anode in the display **300** is connected to another addressable anode of the same color by a straight line bus connection along a seam in any direction. Thus, for example, the green

09997570.010600

anode of pixel **310** is connected by a bus line along the seam to the green anode of pixel **330**. Likewise, the green anode of pixel **310** is also connected by a bus line along the seam to the green anode of pixel **340** and to the green anode of the pixel behind pixel **320**. This structural characteristic aids in addressability of the pixels in that every pixel seam will have only one type of anode or cathode assigned to it.

It should also be noted that the distance between any two adjacent anodes and the distance between adjacent anodes and an adjacent cathode is the same. In other words, each primary electrical component is equidistant from its nearest neighbors in this invention's matrix of pixels. This distance, in the cubical structure shown in **Figure 3**, is equal to the square root of two, times the length of one side of a pixel.

Furthermore, the distance between an electrical component (anode or cathode) and its nearest neighbor of the same type is twice the length of one side of a pixel. This configuration simplifies the calculation necessary to determine signal strength and the specific charges needed for a desired cell output.

**Figure 4** is an exemplary block diagram of a control system **400** for controlling the operation of the three-dimensional display of **Figure 3**. As shown in **Figure 4**, the control system includes a controller **410**, an image input interface **420**, a display interface **430**, and a memory **440**. These elements are in communication with one another via the control/signal bus **450**.

Although a bus architecture is shown in **Figure 4**, other architectures that facilitate the communication between

elements **410-440** may be used without departing from the spirit and scope of the invention.

The controller **410** may be used to determine which pixels **200** of the display to illuminate, which anodes and/or cathodes to charge and the intensity of the charge to each of the anodes and/or cathodes in order to create a desired three-dimensional image input via the image input interface **420**. Using the control system of **Figure 4**, an image is input via the image input interface **420** and temporarily stored in memory **440**. The image input interface **420** may provide a communication pathway from any of a plurality of image sources. For example, the image source may be a computer, television signal receiver, cable system receiver, satellite receiver, storage medium, or the like.

The input image may need to be coded in such a way that the input image data depicts an image in three dimensions. For example, in computer graphical displays, the input image data may consist of three-dimensionally rendered objects which have image data identifying image features with three-dimensional measurements.

The controller **410** pixelizes the input image in three dimensions and sends the pixelized input image to the display interface **430**. The display interface **430** processes the pixelized input image and drives the three-dimensional display **300** to reproduce the image in three dimensions. The pixelization and reproduction of the input image may make use of coordinate system transformation to transform the pixelized input image into data represented in a display coordinate system. Such coordinate transformations are well known to those

054750-010600

of ordinary skill in the art.

**Figures 5A-C** illustrate the manner in which the display **300** of **Figure 3** may be used to generate a three-dimensional image. As shown in **Figure 5**, the controller **410** controls the pixels such that each pixel illuminates a desired color. Those pixels that are not to illuminate or those pixels that are not perceived by a viewer (such as pixels in the center of the display, are not "turned on" by the controller **410** and thus, do not illuminate.

**Figure 5A** shows the display **300** (the full cubical display **300**) with the non-illuminated pixels shown for correlation to the display **300** shown in **Figure 3**. **Figure 5B** shows the display **300** without the non-illuminated pixels but with pixel seams shown. **Figure 5C** shows the display **300** as it would be seen from a human viewer. As shown in **Figure 5C**, the human viewer does not perceive the pixel seams but rather only sees differences in color. Also note that pixel walls that are shared by two pixels and that are illuminated by both pixels will be internal to the three-dimensional image and will not be seen by the viewer.

As an example of the use of the display **300** to produce a three-dimensional image, consider a hollow cylinder, having a square cross-section, standing on one end. In order to display such an image with the display **300**, the outer facing pixels of the display **300** will be illuminated while the center pixels will not be illuminated. Thus, if a viewer is to look at the display from a vantage point slightly above the display, the viewer will see a square shaped top with sides extending

downward. Furthermore, some of the pixels from the side of the cylinder will be seen through the center hole in the cylinder since the center pixels are not illuminated. This in addition to the relative distance between  
5 illuminated pixels allows a viewer to perceive depths in the three-dimensional image.

#### Manufacture of the Three-Dimensional Display

**Figures 6-9** depict a manufacturing process for  
10 manufacturing a three-dimensional display apparatus according to the invention. As shown in **Figure 6**, the first step in manufacturing the three-dimensional display of the present invention is to construct a base **600** for containing the integrated circuitry **620** needed to drive  
15 the display and to distribute all pixel connections to the appropriate "major seam" locations. For example, with a cubical display, such as the cubical display of **Figure 3**, the lower face of the cubical section **300**, may act as the base of the display. The base **600** may be  
20 constructed from, for example, a glass material or silicon material that is etched and has appropriate circuitry deposited thereon.

The major seam is defined as the outermost edge of a cube section, designed to square off all sides of the  
25 section and provide distribution of connections from the base or other major seams. The major seam appropriately routes signals and connections to etched pixel connections, pixel seams, or other major seams. The major seam may also provide structural stability and  
30 weight distribution.

Next, a first "form layer" **700** is created when a

00990884US1

form **710** is pressed to a mold **720** and a glass material, which is secreted into the mold **720**, is thereby manipulated to a desired shape (**Figure 7**). A "form layer" is defined as a layer of partial pixels formed by pressing a form onto a mold. The mold **720** may include electrical components, such as cathodes and anodes, which are to be embedded into the pliant glass as it is pressed into shape while other electrical connections, such as lead lines, may be kept exterior to the glass. The glass is allowed to solidify and the form is then removed.

The mold **720** is pitted with shapes necessary to create one half of a pixel (not including the base or lens). The mold may be pitted in such a way that a plurality of "half pixels" are created with each form layer.

After the glass has solidified, etching is performed to place fine wires, resistors, and the like on the "half pixels." Resistors are placed on the interior walls of the "half pixel" while wirings are placed on the pixel walls and the base **600**. Connections to "major seams" are made along pixel seams. The first layer of wiring for a "major seam" will connect directly to the integrated circuitry of the base **610**.

After etching the wiring patterns and placement of the electrical devices, a protective coating is applied to all exposed surfaces and allowed to set. The protective coating helps to prevent ultraviolet radiation from escaping the pixel cells by reflecting or absorbing them. Additionally, some of this protective material may be chemically included in the glass or similar material used to form the pixel structure, to further protect

primary electrical components from ultraviolet radiation degradation.

Next, the red, green and blue phosphorus material is applied to the appropriate anode, cell wall, or portion of cell wall near the anode. The first form layer **700** is then immersed in a gas filled volume **810** (**Figure 8**), such as a Xenon filled chamber, for example. The first form layer **700** is then applied and sealed to the base **610** using a sealing solution. The pixel faces are shaded in **Figure 8** for purposes of clarity only.

A sealing solution is applied, and a second form layer **920** is then applied to the first form layer **700** (**Figure 9**). To aid in sealing the first form layer **700** to the base **610** and the second form layer **920** to the first form layer **700**, layer connectors (not shown) may be utilized. Layer connectors are juts or small bumps of extra pixel material, such as glass, which are left during the form layer process so that the form layer may be more fully joined with the next form layer or base.

The second form layer **920** is created in the same manner as the first form layer **700** but includes the form corresponding to the other half of the pixels in the first form layer **700** (excluding the upper pixel face). The second form layer **920** may also include the lens **298**.

The sealing solution seals the connection between the two form layers. The side-facing and bottom-facing cells **930** thereby seal in a portion of the gas from the gas filled volume. Next, a top glass plate **940** is applied to the second form layer **920** to thereby seal in a portion of the gas from the gas filled volume in the upper cell **950** of the pixels. Normally, however, an

additional layer of pixels is placed above the first layer of pixels and may serve as its top plate **940**.

After the pixels in a layer have been completed, external wiring and circuitry are added to the layer.

- 5 This external wiring may include anode bus lines, cathode lines, and the like. Preferably, these electrical wirings and bus lines are positioned in the seams between pixels. The process may be repeated as required to complete additional layers of pixels.

- 10 While the above description of the three-dimensional display of the invention makes reference to cubical cells and a cubical display, the invention is not limited to such embodiments. Rather, any shape of the cells and the display may be utilized without departing from the spirit and scope of the present invention. For example, as  
15 shown in **Figures 10A-C**, the pixel **1010** and the cells **1020** may be triangular in shape (**Figure 10B** depicts the base of the pixel **1010**). Furthermore, the display may make use of these triangular shapes to create a display having  
20 a plurality of geometries.

- The description of the present invention has been presented for purposes of illustration and description, but is not intended to be exhaustive or limited to the invention in the form disclosed. Many modifications and  
25 variations will be apparent to those of ordinary skill in the art. The embodiment was chosen and described in order to best explain the principles of the invention, the practical application, and to enable others of ordinary skill in the art to understand the invention for  
30 various embodiments with various modifications as are suited to the particular use contemplated.

05477570.010600

**CLAIMS:**

What is claimed is:

5

1. A three dimensional display, comprising:  
a three dimensional matrix of light emitting  
elements capable of generating images in three  
dimensions; and

10

a base coupled to the three dimensional matrix,  
the base having electrical circuitry for powering and  
controlling the three dimensional matrix.

15

2. The three dimensional display of claim 1, wherein  
the light emitting elements are pixels, and wherein each  
of the pixels has a red light emitting element, a green  
light emitting element, and a blue light emitting  
element.

20

3. The three dimensional display of claim 2, wherein  
the red light emitting element, green light emitting  
element and blue light emitting element are each  
comprised of a cell having an anode, a cathode, a gas  
volume and a phosphorus material.

25

4. The three dimensional display of claim 2, wherein  
the red light emitting element, green light emitting  
element, and blue light emitting element each have an  
anode and a cathode.

30

5. The three dimensional display of claim 2, wherein

00907670.010600

Docket No. AUS990884US1

an anode of one of the pixels is shared by at least one other pixel.

6. The three dimensional display of claim 2, wherein a  
5 face of one of the pixels is shared by another pixel.

7. The three dimensional display of claim 2, wherein a  
top face of a pixel is the bottom face of a neighboring  
pixel, and wherein the side of the pixel is the side of  
10 another neighboring pixel.

8. The three dimensional display of claim 2, wherein  
electrical connections between the pixels, signal sources  
and power sources are positioned in seams between pixels.  
15

9. The three dimensional display of claim 2, wherein an  
anode bus line is positioned in a seam from a first anode  
of a pixel to a second anode of another pixel.

10. The three dimensional display of claim 2, wherein a  
first anode of a first red light emitting element of a  
pixel is connected to a second anode of a second red  
light emitting element in another pixel by a straight  
line bus connection along a seam in any direction in the  
25 three dimensional matrix.

11. The three dimensional display of claim 2, wherein a  
first anode of a first green light emitting element of a  
pixel is connected to a second anode of a second green  
30 light emitting element in another pixel by a straight  
line bus connection along a seam in any direction in the  
three dimensional matrix.

094750-010600

12. The three dimensional display of claim 2, wherein a first anode of a first blue light emitting element of a pixel is connected to a second anode of a second blue light emitting element in another pixel by a straight line bus connection along a seam in any direction in the three dimensional matrix.
13. The three dimensional display of claim 2, wherein a first cathode of a first pixel is connected to a second cathode of a second pixel by a straight line connection along a seam in any direction in the three dimensional matrix.
14. The three dimensional display of claim 2, wherein the distance between two adjacent anodes is a square root of two multiplied by a length of one side of a pixel.
15. The three dimensional display of claim 10, wherein a distance between the first anode and the second anode of the first red light emitting element and the second red light emitting element is twice the length of one side of a pixel.
16. The three dimensional display of claim 13, wherein a distance between the first cathode and the second cathode of first pixel and the second pixel is twice the length of one side of a pixel.
17. The three dimensional display of claim 11, wherein the distance between the first anode and the second anode of the first green light emitting element and the second

09477570-010600

Docket No. AUS990884US1

green light emitting element is twice the length of one side of a pixel.

18. The three dimensional display of claim 12, wherein  
5 the distance between the first anode and the second anode of the first blue light emitting element and the second blue light emitting element is twice the length of one side of a pixel.

10 19. The three dimensional display of claim 1, further comprising a control system that controls which of the light emitting elements in the three dimensional matrix are illuminated.

15 20. The three dimensional display of claim 19, wherein the control system controls color, intensity and duration of the light emitted by the light emitting elements in the three dimensional matrix.

20 21. The three dimensional display of claim 19, wherein the control system receives an input image coded in a three dimensional coordinate system.

22. The three dimensional display of claim 21, wherein  
25 the input image is received from one of a computer, television signal receiver, cable system receiver, satellite receiver, and a storage medium.

23. The three dimensional display of claim 21, wherein  
30 the control system pixelizes the input image for reproduction by the three dimensional display.

009070-0252460

Docket No. AUS990884US1

24. The three dimensional display of claim 1, wherein the three dimensional matrix has a cube shape.

25. A three dimensional display, comprising:

5 a plurality of three dimensional light emitting elements configured to emit light in three dimensions; and

a controller that controls the operation of the light emitting elements to generate a three dimensional  
10 image.

26. The three dimensional display of claim 25, wherein the light emitting elements are pixels, and wherein each of the pixels has a red light emitting element, a green  
15 light emitting element, and a blue light emitting element.

27. The three dimensional display of claim 26, wherein the red light emitting element, green light emitting  
20 element and blue light emitting element are each comprised of a cell having an anode, a cathode, a gas volume and a phosphorus material.

28. The three dimensional display of claim 26, wherein a  
25 cathode of one of the pixels is shared by one or more other pixels.

29. The three dimensional display of claim 26, wherein the red light emitting element, green light emitting  
30 element, and blue light emitting element each have an anode and a cathode.

09477570-010600

Docket No. AUS990884US1

30. The three dimensional display of claim 26, wherein an anode of one of the pixels is shared by one or more other pixels.

5 31. The three dimensional display of claim 26, wherein a face of one of the pixels is shared by another pixel.

32. The three dimensional display of claim 26, wherein a top face of a pixel is the bottom face of a neighboring  
10 pixel, and wherein the side of a pixel is the side of another neighboring pixel.

33. The three dimensional display of claim 26, wherein electrical connections between the pixels, signal sources  
15 and power sources are positioned in seams between pixels.

34. The three dimensional display of claim 26, wherein an anode bus line is positioned in a seam from an anode of a pixel to an anode of another pixel.  
20

35. The three dimensional display of claim 26, wherein a cathode line is positioned in a seam from a cathode of one pixel to a cathode of another pixel.

25 36. The three dimensional display of claim 26, wherein an anode of a red light emitting element of a pixel is connected to another anode of a red light emitting element in another pixel by a straight line bus connection along a seam in any direction.

30 37. The three dimensional display of claim 26, wherein an anode of a green light emitting element of a pixel is

0090750-010600

Docket No. AUS990884US1

connected to another anode of a green light emitting element in another pixel by a straight line bus connection along a seam in any direction.

- 5 38. The three dimensional display of claim 26, wherein an anode of a blue light emitting element of a pixel is connected to another anode of a blue light emitting element in another pixel by a straight line bus connection along a seam in any direction.

10

39. The three dimensional display of claim 26, wherein a first cathode of a first pixel is connected to a second cathode of a second pixel by a straight line connection along a seam in any direction.

15

40. The three dimensional display of claim 26, wherein the distance between two adjacent anodes is the square root of two times the length of one side of a pixel.

20

41. The three dimensional display of claim 36, wherein the distance between the anodes of the red light emitting elements is twice the length of one side of a pixel.

25

42. The three dimensional display of claim 37, wherein the distance between the anodes of the green light emitting elements is twice the length of one side of a pixel.

30

43. The three dimensional display of claim 38, wherein the distance between the anodes of the blue light emitting elements is twice the length of one side of a pixel.

009070-022450

Docket No. AUS990884US1

44. The three dimensional display of claim 39, wherein the distance between the first cathode and the second cathode is twice the length of one side of a pixel.

5

45. The three dimensional display of claim 25, wherein the controller controls the color, intensity and duration of the light emitted by the light emitting elements.

10 46. The three dimensional display of claim 25, wherein the controller receives an input image that is coded in a three dimensional coordinate system.

15 47. The three dimensional display of claim 46, wherein the input image is received from one of a computer, television signal receiver, cable system receiver, satellite receiver, and a storage medium.

20 48. The three dimensional display of claim 46, wherein the control system pixelizes the input image for reproduction by the three dimensional display.

25 49. The three dimensional display of claim 25, wherein the light emitting elements are formed into a matrix having a cube shape.

00990884US1

**ABSTRACT OF THE DISCLOSURE**

5

**Three-Dimensional Display Apparatus**

10 A three-dimensional display apparatus capable of  
producing an image in three dimensions without the aid of  
optical illusions or perspective trickery. The display  
apparatus is comprised of a plurality of pixels which  
are, in turn, comprised of a plurality of cells. The  
cells illuminate in one of the three primary colors red,  
green and blue such that a combination of a red, green  
15 and blue cell into a pixel, is capable of producing any  
color in the visible spectrum. The cells are oriented in  
the pixel such that light from the pixel is perceivable  
in six directions, thereby creating a three-dimensional  
light source. By combining a plurality of these  
20 three-dimensional light sources, i.e. a plurality of  
pixels in a three-dimensional matrix, a three-dimensional  
image is capable of being displayed.

009070"02450




Figure 1

AUS990884US1  
Sheet 1 of 11

009070"07572450




Figure 2A

AUS990884US1  
Sheet 2 of 11

009070"07672450




Figure 2B

005070" 02542460




Figure 3

AUS990884US1  
Sheet 4 of 11

009070" 0252450




Figure 4

009070" 0252450

Figure 5A





Figure 5B




Figure 5C

009070"02522450




Figure 6

AUS990884US1  
Sheet 7 of 11

009070"0452450

700




Figure 7

AUS990884US1  
Sheet 8 of 11

09477570.040600




Figure 8

AUS990884US1  
Sheet 9 of 11




Figure 9

AUS990884US1  
Sheet 10 of 11

Figure 10A





Figure 10C




Figure 10B

DECLARATION AND POWER OF ATTORNEY FOR  
PATENT APPLICATION

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name;

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

THREE-DIMENSIONAL DISPLAY APPARATUS

the specification of which (check one)

X is attached hereto.

— was filed on \_\_\_\_\_  
as Application Serial No. \_\_\_\_\_  
and was amended on \_\_\_\_\_  
(if applicable)

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the patentability of this application in accordance with Title 37, Code of Federal Regulations, §1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s):			Priority Claimed
_____	_____	_____	Yes No
(Number)	(Country)	(Day/Month/Year)	

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose information material to the patentability of this application as defined in Title 37, Code of Federal Regulations, §1.56 which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

_____	_____	_____
(Application Serial #)	(Filing Date)	(Status)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorneys and/or agents to prosecute this application and transact all business in the Patent and Trademark Office connected therewith.

John W. Henderson, Jr., Reg. No. 26,907; Thomas E. Tyson, Reg. No. 28,543; James H. Barksdale, Jr., Reg. No. 24,091; Casimer K. Salys, Reg. No. 28,900; Robert M. Carwell, Reg. No. 28,499; Douglas H. Lefevre, Reg. No. 26,193; Jeffrey S. LaBaw, Reg. No. 31,633; David A. Mims, Jr., Reg. 32,708; Volel Emile, Reg. No. 39,969; Anthony V. England, Reg. No. 35,129; Leslie A. Van Leeuwen, Reg. No. 42,196; Christopher A. Hughes, Reg. No. 26,914; Edward A. Pennington, Reg. No. 32,588; John E. Hoel, Reg. No. 26,279; Joseph C. Redmond, Jr., Reg. No. 18,753; Marilyn S. Dawkins, Reg. No. 31,140; Mark E. McBurney, Reg. No. 33,114; Duke W. Yee, Reg. No. 34,285; Colin P. Cahoon, Reg. No. 38,836; Joseph R. Burwell, Reg. No. 44,468; Rudolph J. Buchel, Reg. No. 43,448; and Stephen R. Loe, Reg. No. 43,757; Stephen J. Walder, Reg. No. 41,534.

Send correspondence to: Duke W. Yee, Carstens, Yee & Cahoon, LLP, P.O. Box 802334, Dallas, Texas 75380 and direct all telephone calls to Duke W. Yee, (972) 362-2001

FULL NAME OF SOLE OR FIRST INVENTOR: Daniel J. Knabenbauer

INVENTORS SIGNATURE:  DATE: 12/10/99

RESIDENCE: 18755 Lemay Street  
Reseda, California 91335-5239

CITIZENSHIP: United States  
POST OFFICE ADDRESS: SAME AS ABOVE

00990884US1